

Network Working Group	M. Douglass
Internet-Draft	Spherical Cow Group
Updates: 5988,7240 (if approved)	June 7, 2019
Intended status: Standards Track	
Expires: December 9, 2019	

Calendar subscription upgrades

draft-ietf-calext-subscription-upgrade-00

Abstract

This specification introduces an approach to allow subscribers to calendar feeds to upgrade to a more performant protocol.

This specification updates [\[RFC5545\]](#) to add the value DELETED to the STATUS property.

This specification also updates [\[RFC7240\]](#) to add the subscribe- enhanced-get and limit preferences.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on December 9, 2019.

Copyright Notice

Copyright (c) 2019 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

- 1. Introduction**
 - 1.1. Terms and Definitions**
- 2. Discovering alternative access methods**
- 3. Enhanced GET**
 - 3.1. General**
 - 3.2. Deletions**
 - 3.3. Handling of invalid sync tokens**
 - 3.4. Paging the response**
 - 3.5. Caching of responses**
 - 3.6. Examples**
- 4. Changes to the iCalendar specifications**
 - 4.1. Redefined Status property**
- 5. Header Field: Sync-Token**
- 6. New Prefer header field preferences**
 - 6.1. Preference subscribe-enhanced-get**
 - 6.2. Preference limit**
- 7. Link relations**
 - 7.1. General**
 - 7.2. subscribe-caldav**
 - 7.3. subscribe-caldav-auth**
 - 7.4. subscribe-webdav-sync**
 - 7.5. subscribe-enhanced-get**
- 8. Security Considerations**
- 9. IANA Considerations**
 - 9.1. Sync-Token HTTP Header Field Registration**
 - 9.2. Preference Registrations**
 - 9.3. Link Relation Registrations**
- 10. Acknowledgements**
- 11. Normative References**
- Appendix A. Open issues**
- Appendix B. Change log**
- Author's Address**

1. Introduction

Currently clients subscribe to calendar feeds as an iCalendar file which is often published as a resource accessible using the unofficial 'webcal' scheme.

The only available option for updating that resource is the usual HTTP polling of cached resources using Etags.

There is the usual tension between clients wishing to see a timely response to changes and servers not wishing to be overloaded by frequent requests for possibly large amounts of data.

This specification introduces an approach whereby clients can discover a more performant access method. Given the location of the resource as an iCalendar file, the client can perform a HEAD request on the resource and inspect the returned headers which will offer a number of alternative access methods.

Given that many clients and servers already support CalDAV this provides an easy upgrade path for those clients. CalDAV and DAV subsets are specified here to allow lighter weight implementations.

1.1. Terms and Definitions

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in BCP 14 [RFC2119] [RFC8174] when, and only when, they appear in all capitals, as shown here.

Additionally, the rule for URI is included from [RFC3986].

2. Discovering alternative access methods

The advertising of other access points is achieved through the use of the LINK header as defined in [RFC5988]. New link relation types are defined in this specification - each being associated with a protocol or protocol subset.

These LINK headers will be delivered when a client carries out a HEAD request targeting the URL of the resource.

This is an example of a HEAD request and the response from a server that supports the enhanced GET method.

```
>> Request <<

HEAD /caldata/events.ics HTTP/1.1
Host: example.com
Accept: text/calendar

>> Response <<

HTTP/1.1 200 OK
Content-Length: xxxx
Link: <http://example.com/subscribe/events.ics>;
      rel="subscribe-enhanced-get"
```

Note that the target for an upgraded service may be the same as for the initial resource.

3. Enhanced GET

3.1. General

This is a lightweight protocol which allows simple clients to efficiently discover and download changes in the targeted resource.

It has many similarities to WebDAV sync and for a server could be implemented as an extension of the specification.

In this protocol the client MUST include the Prefer header field preference "subscribe-enhanced-get". If a sync token is available it is passed as a Sync-Token header field.

The resource is treated as a set of individual events each of which may be updated or deleted separately. The client will first fetch the entire iCalendar file. On subsequent requests it uses the Prefer header field and a Sync-Token header field to indicate that it wants a set of changes since the last fetch.

If no Sync-Token header field is supplied the server SHOULD respond with a full set of data. Otherwise, if the token is valid, it SHOULD return with a set of changed entities.

In both cases the server should set the Preference-Applied header field and a new Sync-Token header field

value.

3.2. Deletions

When an entity (VEVENT, VTODO or other valid top-level component) is deleted from the source data the server needs to be able to inform a client of the deletion. This specification introduces a new value for the STATUS property of DELETED.

On the first enhanced GET after the entity has been deleted a skeleton, but valid, entity will be returned with STATUS: DELETED. The receiving client is free to remove the entity or update it's STATUS property.

On subsequent fetches the entity will not be returned.

3.3. Handling of invalid sync tokens

When a server receives an invalid token it MUST return a 409 status (Conflict). The server MAY choose to return an error message in the body.

The client SHOULD respond to this error by restarting the interaction from scratch, i.e. retrieve the full set of data then poll for updates.

3.4. Paging the response

A client may explicitly request a limit on the size of the response by specifying the Prefer header field preference "limit=n" where n is the number of components.

When a server receives a request specifying such a limit it SHOULD limit the response to that number of components. If the limit causes a truncation in the response the server should respond with a Preference-Applied header specifying the limit that was applied and return a sync token which may be used to retrieve the next batch of data.

This allows the client to immediately resubmit a request for the next batch using the updated token.

A server MAY choose to limit the response size. The behavior SHOULD be as if the client had provided a preference for that size - allowing the client to retrieve the full set of data in batches.

3.5. Caching of responses

To enable proper caching of responses the server SHOULD provide a VARY header field in responses that names the Prefer and Sync-Token header fields along with any other that are appropriate.

Clients should order the preferences as following so that identical responses can be identified:

- subscribe-enhanced-get
- limit

3.6. Examples

This is an example of the initial request and response from a server that supports the enhanced GET method. Note the use of the Vary header so a caching proxy can key off the client's Sync-Token and preference.

```
>> Request <<
```

```
GET /events.ics HTTP/1.1
```

```
Host: example.com
```

```
Accept: text/calendar
```

```
Prefer: subscribe-enhanced-get
```

```
>> Response <<
```

```
HTTP/1.1 200 OK  
Content-Length: xxxx  
Sync-Token: "data:,1234567"  
Preference-Applied: subscribe-enhanced-get  
Vary: Prefer, Sync-Token
```

```
BEGIN:VCALENDAR:  
? /* full feed */  
END:VCALENDAR
```

This is an example of the subsequent request and response when no changes have occurred.

```
>> Request <<
```

```
GET /events.ics HTTP/1.1  
Host: example.com  
Accept: text/calendar  
Prefer: subscribe-enhanced-get  
Sync-Token: "data:,1234567"
```

```
>> Response <<
```

```
HTTP/1.1 304 Not Modified  
Content-Length: 0  
Sync-Token: "data:,1234567"  
Preference-Applied: subscribe-enhanced-get  
Vary: Prefer, Sync-Token
```

This is an example of the subsequent request and response for an old or invalid token.

```
>> Request <<
```

```
GET /events.ics HTTP/1.1  
Host: example.com  
Accept: text/calendar  
Sync-Token: "data:,1234567"  
Prefer: subscribe-enhanced-get
```

```
>> Response <<
```

```
HTTP/1.1 409 Conflict  
Content-Length: xxxx  
Preference-Applied: subscribe-enhanced-get
```

This is an example of the subsequent request and response when changes have occurred.

```
>> Request <<
```

```
GET /events.ics HTTP/1.1
```

```
Host: example.com
Accept: text/calendar
Sync-Token: "data:,1234567"
Prefer: subscribe-enhanced-get
```

>> Response <<

```
HTTP/1.1 200 OK
Content-Type: text/calendar
Vary: Prefer, Sync-Token
Sync-Token: "data:,4567890"
Preference-Applied: subscribe-enhanced-get
```

```
BEGIN:VCALENDAR:
... only new/changed events
... deleted events have STATUS:DELETED
END:VCALENDAR
```

4. Changes to the iCalendar specifications

This specification updates [\[RFC5545\]](#) to add the value DELETED to the STATUS property.

4.1. Redefined Status property

Property name

STATUS

Purpose

This property defines the overall status or confirmation for the calendar component.

Value Type

TEXT

Property Parameters

IANA and non-standard property parameters can be specified on this property.

Conformance

This property can be specified once in "VEVENT", "VTODO", or "VJOURNAL" calendar components.

Description

In a group-scheduled calendar component, the property is used by the "Organizer" to provide a confirmation of the event to the "Attendees". For example in a "VEVENT" calendar component, the "Organizer" can indicate that a meeting is tentative, confirmed, or cancelled. In a "VTODO" calendar component, the "Organizer" can indicate that an action item needs action, is completed, is in process or being worked on, or has been cancelled. In a "VJOURNAL" calendar component, the "Organizer" can indicate that a journal entry is draft, final, or has been cancelled or removed.

Format Definition

This property is defined by the following notation:

```
status = "STATUS" statparam ":" statvalue CRLF
```

```

statparam    = *(";" other-param)

statvalue    = (statvalue-event
                / statvalue-todo
                / statvalue-jour)

statvalue-event = "TENTATIVE" ;Indicates event is tentative.
                / "CONFIRMED" ;Indicates event is definite.
                / "CANCELLED" ;Indicates event was cancelled.
                / "DELETED"   ;Indicates event was deleted.
;Status values for a "VEVENT"

statvalue-todo = "NEEDS-ACTION" ;Indicates to-do needs action.
                / "COMPLETED"  ;Indicates to-do completed.
                / "IN-PROCESS"  ;Indicates to-do in process of.
                / "CANCELLED"   ;Indicates to-do was cancelled.
                / "DELETED"     ;Indicates to-do was deleted.
;Status values for "VTODO".

statvalue-jour = "DRAFT"       ;Indicates journal is draft.
                / "FINAL"      ;Indicates journal is final.
                / "CANCELLED"  ;Indicates journal is removed.
                / "DELETED"    ;Indicates journal was deleted.
;Status values for "VJOURNAL".

```

Example

The following is an example of this property for a "VEVENT" calendar component:

```
STATUS:TENTATIVE
```

The following is an example of this property for a "VTODO" calendar component:

```
STATUS:NEEDS-ACTION
```

The following is an example of this property for a "VJOURNAL" calendar component:

```
STATUS:DRAFT
```

5. Header Field: Sync-Token

This specification defines a new header field Sync-Token for use by the enhanced GET method.

```
Accept = DQUOTE URI DQUOTE
```

The value MUST be a URI. This will generally be a data URI representing an opaque token. Client MUST not attempt to interpret the data URI value.

This is an example of the Sync-Token header field:

```
Sync-Token: "data:,1234567"
```

6. New Prefer header field preferences

6.1. Preference subscribe-enhanced-get

This indicates that the client expects the server to handle the GET method according to the specifications for enhanced get.

```
pref-subscribe-enhanced-get = "subscribe-enhanced-get"
```

6.2. Preference limit

This preference parameter provides a limit on the number of components returned for enhanced get.

```
pref-limit = "limit" BWS "=" BWS 1*DIGIT
```

7. Link relations

7.1. General

This clause defines a number of new link relations required to facilitate subscription upgrades.

7.2. subscribe-caldav

This specifies an access point which is a full implementation of caldav but requires no authentication. The end point allows the full range of reports as defined by the CalDAV specification.

The client **MUST** follow the specification to determine exactly what operations are allowed on the access point - for example to determine if sync-report is supported.

The URL **MAY** include some form of token to allow write access to the targeted collection. The client must check it's permissions to determine whether or not it has been granted write access.

7.3. subscribe-caldav-auth

This specifies an access point which is a full implementation of caldav and requires authentication. This may allow read-write access to the resource.

The client **MUST** follow the specification to determine exactly what operations are allowed on the access point — for example to determine if sync-report is supported.

7.4. subscribe-webdav-sync

This specifies an access point which supports only webdav sync.

This allows the client to issue a sync-report on the resource to obtain updates.

The client **MUST** follow that specification.

7.5. subscribe-enhanced-get

This specifies an access point which supports something new.

The client **MUST** follow that specification.

8. Security Considerations

Applications using these properties need to be aware of the risks entailed in using the URIs provided as values. See [\[RFC3986\]](#) for a discussion of the security considerations relating to URIs. == Privacy

Considerations

Properties with a "URI" value type can expose their users to privacy leaks as any network access of the URI data can be tracked. Clients SHOULD NOT automatically download data referenced by the URI without explicit instruction from users. This specification does not introduce any additional privacy concerns beyond those described in [\[RFC5545\]](#).

9. IANA Considerations

9.1. Sync-Token HTTP Header Field Registration

This specification updates the "Message Headers" registry entry for "Sync-Token" in [\[RFC3864\]](#) to refer to this document.

```
Header Field Name: Sync-Token
Protocol: http
Status: standard
Reference: <this-document>
```

9.2. Preference Registrations

The following preferences have been added to the HTTP Preferences Registry defined in [\[RFC7240\]](#)

Preference

subscribe-enhanced-get

Value

None.

Description

Marks the interaction as enhanced get and provides the optional sync-token and page size.

Reference

this document

Preference

limit

Value

An integer page size.

Description

Provide a limit on the number of components in the response.

Reference

this document

9.3. Link Relation Registrations

This document defines the following new iCalendar properties to be added to the registry defined in [section=8.2.3](#):

Relation Name	Description	Reference
subscribe-caldav	Current	Section 7.2
subscribe-caldav_auth	Current	Section 7.3
subscribe-webdav-sync	Current	Section 7.4
subscribe-enhanced_get	Current	Section 7.5

10. Acknowledgements

The author would also like to thank the members of the CalConnect Calendar Sharing technical committee and the following individuals for contributing their ideas and support:

Marten Gajda, Ken Murchison, Garry Shutler

The authors would also like to thank CalConnect, the Calendaring and Scheduling Consortium, for advice with this specification.

11. Normative References

- [RFC2119] Bradner, S., "[Key words for use in RFCs to Indicate Requirement Levels](#)", BCP 14, RFC 2119, DOI 10.17487/RFC2119, March 1997.
- [RFC2434] Narten, T. and H. Alvestrand, "[Guidelines for Writing an IANA Considerations Section in RFCs](#)", RFC 2434, DOI 10.17487/RFC2434, October 1998.
- [RFC3688] Mealling, M., "[The IETF XML Registry](#)", BCP 81, RFC 3688, DOI 10.17487/RFC3688, January 2004.
- [RFC3864] Klyne, G., Nottingham, M. and J. Mogul, "[Registration Procedures for Message Header Fields](#)", BCP 90, RFC 3864, DOI 10.17487/RFC3864, September 2004.
- [RFC3986] Berners-Lee, T., Fielding, R. and L. Masinter, "[Uniform Resource Identifier \(URI\): Generic Syntax](#)", STD 66, RFC 3986, DOI 10.17487/RFC3986, January 2005.
- [RFC4589] Schulzrinne, H. and H. Tschofenig, "[Location Types Registry](#)", RFC 4589, DOI 10.17487/RFC4589, July 2006.
- [RFC5545] Desruisseaux, B., "[Internet Calendaring and Scheduling Core Object Specification \(iCalendar\)](#)", RFC 5545, DOI 10.17487/RFC5545, September 2009.
- [RFC5546] Daboo, C., "[iCalendar Transport-Independent Interoperability Protocol \(iTIP\)](#)", RFC 5546, DOI 10.17487/RFC5546, December 2009.
- [RFC5988] Nottingham, M., "[Web Linking](#)", RFC 5988, DOI 10.17487/RFC5988, October 2010.
- [RFC6578] Daboo, C. and A. Quillaud, "[Collection Synchronization for Web Distributed Authoring and Versioning \(WebDAV\)](#)", RFC 6578, DOI 10.17487/RFC6578, March 2012.
- [RFC7240] Snell, J., "[Prefer Header for HTTP](#)", RFC 7240, DOI 10.17487/RFC7240, June 2014.
- [RFC7991] Hoffman, P., "[The "xml2rfc" Version 3 Vocabulary](#)", RFC 7991, DOI 10.17487/RFC7991, December 2016.
- [RFC8174] Leiba, B., "[Ambiguity of Uppercase vs Lowercase in RFC 2119 Key Words](#)", BCP 14, RFC 8174, DOI 10.17487/RFC8174, May 2017.

Appendix A. Open issues

Vary

Ensure we get that right.

Appendix B. Change log

calext00 2019-06-05 MD

- First calext version
- Use Sync-Token header rather than parameter

v04 2019-03-07 MD

- Reference to RFC 6538 - WebDAV sync and RFC 7240 Prefer
- Go back to HEAD
- New Preference and parameters.
- Examples
- More text for extended get. Talk about deletions.

v01 2017-02-17 MD

- Add text about OPTIONS
- Add text about read/write CalDAV

v00 2017-02-15 MD

- First pass

Author's Address

Michael Douglass

Spherical Cow Group

226 3rd Street

Troy, 12180

United States of America

Email: mdouglass@sphericalcowgroup.com

URI: <http://sphericalcowgroup.com>